
# **Product datasheet**

Specifications







Local distributor code: 397362338 A9XPH312

#### Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L
Length in 18 mm modules	12

#### Complementary

Complementary	
Number of ways	4 ways 3 L
Poles configuration for 1 way	1 x 3P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	54 mm
Marking	L1 L2 L3
Insulation	Insulated
Device presentation	Cuttable
[le] rated operational current	100 A at 40 °C
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top or bottom on tunnel type terminals Top or bottom on double terminal
9 mm pitches	24
Width	220 mm
Colour	White (RAL 9003)
Range compatibility	Acti9 iC60 Acti9 iK60 Acti9 iID Acti9 iID K Acti9 iSW Acti9 iSW Acti9 iSW-NA Multi 9 C60

#### **Environment**

Standards	IEC 60947-7-1 IEC 61439-2
Fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1
Pollution degree	3 conforming to IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	108.0 g
Package 1 Height	3 cm
Package 1 width	1.6 cm
Package 1 Length	21.2 cm
Unit Type of Package 2	P12
Number of Units in Package 2	1920
Package 2 Weight	244.56 kg
Package 2 Height	105 cm
Package 2 width	
Tackage 2 Width	80 cm
Package 2 Length	80 cm 120 cm
Package 2 Length	120 cm
Package 2 Length Unit Type of Package 3	120 cm BB1
Package 2 Length  Unit Type of Package 3  Number of Units in Package 3	120 cm  BB1 5
Package 2 Length  Unit Type of Package 3  Number of Units in Package 3  Package 3 Weight	120 cm  BB1  5  607.0 g
Package 2 Length  Unit Type of Package 3  Number of Units in Package 3  Package 3 Weight  Package 3 Height	120 cm  BB1  5  607.0 g  6 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### **Contractual warranty**

Warranty 18 months
--------------------