Product datasheet

Specifications



Acti9 - comb busbar - 1L - 18 mm pitch - 57 modules - 100A

Local distributor code: 397362639 A9XPH157

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	1L
Length in 18 mm modules	57

Complementary

Complementary	
Number of ways	57 ways 1 L
Poles configuration for 1 way	1 x 1P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	18 mm
Marking	L
Insulation	Insulated
Device presentation	Cuttable
Provided equipment	Set of 10 end piece
[le] rated operational current	100 A at 40 °C
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top or bottom on tunnel type terminals Top or bottom on double terminal
9 mm pitches	114
Width	1000 mm
Colour	White (RAL 9003)
Range compatibility	Acti9 iC60 Acti9 iK60 Acti9 iID Acti9 iID K Acti9 iSW Acti9 iSW-NA Multi 9 C60

Environment

Standards	IEC 60947-7-1 IEC 61439-2
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3 conforming to IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	234.0 g
Package 1 Height	0.52 cm
Package 1 width	0.9 cm
Package 1 Length	106 cm
Unit Type of Package 2	P12
Number of Units in Package 2	270
Package 2 Weight	88.734 kg
Package 2 Height	112 cm
Package 2 width	80 cm
Package 2 Length	120 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	1.376 kg
Package 3 Height	5.2 cm
Package 3 width	106.5 cm
Package 3 Length	9 cm

Offer Sustainability

Green Premium product
REACh Declaration
Yes
Compliant EU RoHS Declaration
Yes
Yes
Yes
China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty 18 months
