

# Product datasheet

Specifications



## current transformer tropicalised 400 5 double output for bars 32x65

Local distributor code: 397546316 METSECT5DA040

### Main

|                           |                                      |
|---------------------------|--------------------------------------|
| Range                     | PowerLogic                           |
| Product name              | CT                                   |
| Product or component type | Current transformer                  |
| Secondary current         | 5 A                                  |
| Accuracy class            | Class 0.5 at 4 VA<br>Class 1 at 8 VA |
| [In] rated current        | 400 A                                |

### Complementary

|   |                                |
|---|--------------------------------|
| Current transformer type                    | Tropicalised for busbar        |
| Current transformer ratio                   | 400/5                          |
| [Ith] conventional free air thermal current | 24 kA                          |
| Dynamic withstand current                   | 2.5 Ith                        |
| Maximum safety factor                       | 5                              |
| [Ue] rated operational voltage              | < 720 V AC 50/60 Hz            |
| [Ui] rated insulation voltage               | 3 kV                           |
| Mounting mode                               | Insulated locking screw        |
| Mounting support                            | Busbar                         |
| Width                                       | 90 mm outside:<br>65 mm inner: |
| Height                                      | 94 mm outside:<br>32 mm inner: |
| Depth                                       | 40 mm frame:<br>87 mm total:   |
| Net weight                                  | 0.531 kg                       |
| [Uimp] rated impulse withstand voltage      | 3 kV                           |
| Electrical insulation class                 | Class B                        |
| Opening of bars                             | 65 x 32                        |
| Sealing                                     | With                           |

## Environment

|                                       |                         |
|---------------------------------------|-------------------------|
| Standards                             | VDE 0414<br>IEC 61869-2 |
| Product certifications                | EAC<br>CE               |
| IP degree of protection               | IP20                    |
| Relative humidity                     | 0...95 %                |
| Ambient air temperature for operation | -25...60 °C             |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 480.0 g  |
| Package 1 Height             | 10.4 cm  |
| Package 1 width              | 9.5 cm   |
| Package 1 Length             | 10 cm    |
| Unit Type of Package 2       | S03      |
| Number of Units in Package 2 | 16       |
| Package 2 Weight             | 8.743 kg |
| Package 2 Height             | 30 cm    |
| Package 2 width              | 30 cm    |
| Package 2 Length             | 40 cm    |

## Offer Sustainability

|                          |   |
|--------------------------|---|
| EU RoHS Directive        | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| China RoHS Regulation    | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile      | <a href="#">End of Life Information</a>   |
| WEEE                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|