

Product datasheet

Specifications



current transformer tropicalised DIN mount 400 5 cables d. 27 - bars 10x32 15x25

Local distributor code: 397547441 METSECT5MA040

Main

Range	PowerLogic
Product name	CT
Product or component type	Current transformer
Secondary current	5 A
Accuracy class	Class 0.5 at 10 VA Class 1 at 12 VA
[In] rated current	400 A

Complementary

Current transformer type	Tropicalised for busbar and cable
Current transformer ratio	400/5
[Ith] conventional free air thermal current	24 kA
Dynamic withstand current	2.5 Ith
Maximum safety factor	5
[Ue] rated operational voltage	< 720 V AC 50/60 Hz
[Ui] rated insulation voltage	3 kV
Mounting mode	Clip-on By screws Insulated locking screw
Mounting support	DIN rail Busbar Mounting plate
Width	56 mm outside:
Height	80 mm outside:
Depth	43 mm frame: 63 mm total:
Diameter	27 mm
Net weight	0.328 kg
[Uimp] rated impulse withstand voltage	3 kV
Electrical insulation class	Class B
Cable outer diameter	27 mm
Opening of bars	25.5 x 15.5

32.5 x 10.5

Sealing	Without
---------	---------

Environment

Standards	VDE 0414 IEC 61869-2
-----------	-------------------------

Product certifications	EAC CE
------------------------	-----------

IP degree of protection	IP20
-------------------------	------

Relative humidity	0...95 %
-------------------	----------

Ambient air temperature for operation	-25...60 °C
---------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Weight	322.0 g
------------------	---------

Package 1 Height	7.2 cm
------------------	--------

Package 1 width	7.2 cm
-----------------	--------

Package 1 Length	9.4 cm
------------------	--------

Unit Type of Package 2	S03
------------------------	-----

Number of Units in Package 2	55
------------------------------	----

Package 2 Weight	19.022 kg
------------------	-----------

Package 2 Height	30 cm
------------------	-------

Package 2 width	30 cm
-----------------	-------

Package 2 Length	40 cm
------------------	-------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

REACH free of SVHC	Yes
--------------------	-----

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Mercury free	Yes
--------------	-----

RoHS exemption information	Yes
----------------------------	---------------------

China RoHS Regulation	China RoHS declaration
-----------------------	--

Environmental Disclosure	Product Environmental Profile
--------------------------	---

Circularity Profile	End of Life Information
---------------------	---

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

Contractual warranty

Warranty	18 months
----------	-----------
