

Vigi C120 - earth leakage add-on block - 4P - 300 mA - class A si

Local distributor code: 402641180

Main

Product or component type	Add-on residual current devices
Device short name	Vigi C120
Poles description	4P
[In] rated current	125 A
Network type	AC
Earth-leakage sensitivity	300 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type A-SI (Super Immunised)

Complementary	
Device location in system	Outgoer
Network frequency	50 Hz
[Ue] rated operational voltage	230415 V AC 50 Hz
Residual current tripping technology	Voltage independent
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60947-1
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-2
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
Electrical connection to mcb	By screws
9 mm pitches	10
Height	95 mm
Width	198 mm
Depth	73 mm
Net weight	0.58 kg
Colour	White
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals 135 mm² flexible Tunnel type terminals 150 mm² rigid

Wire stripping length	15 mm
	3.5 N.m
Fightening torque	3.3 IV.III
Environment	
Standards	EN 61009
P degree of protection	IP20
Pollution degree	3 conforming to IEC 60947-2
Ambient air temperature for operation	-2560 °C
Ambient air temperature for storage	-4060 °C
Packing Units	
Jnit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	675.0 g
Package 1 Height	9.3 cm
Package 1 width	13.7 cm
Package 1 Length	25.6 cm
Jnit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Weight	5.879 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Offer Sustainability	
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months