



Spacial S3D seismic plain door with mount.plate - H800xW600xD300 - IP65 - IK10

Local distributor code: 402657857 NSYS3D6G8630P

V	ı	a	ı	r	1

Range	Spacial
Product name	S3D 6G
Enclosure application	Seismic
Product or component type	Enclosure
Enclosure nominal height	800 mm
Enclosure nominal width	600 mm
Enclosure nominal depth	300 mm
Door type	Plain
Mounting plate description	Reinforce
Enclosure mounting	Wall mounted
Device composition	1 x body 1 x door 1 x lock 2 x fixing bracket 1 x mounting plate 1 x earthing components door and lock 1 x cable gland plate
Continuity of earth	Earthing connection between body and door

Complementary

Body type	Single piece body Gutter-shaped front rail
Number of doors	Front face: 1 door(s)
Door opening side	Right (120 °)
Lock type	3-point closure
Type of keylock	EDF 1600
Type of operating handle	Swing handle
Accessibility for operation	Front
Removable parts	Cable gland plate by screws
Material	Steel
Thickness	Body: 2 mm Door: 2 mm Cable gland plate: 1.5 mm
Surface finish	Epoxy-polyester powder

Colour	Grey (RAL 7035)	
Net weight	47 kg	
Environment		
Surface treatment	87 % decontaminable painting conforming to NF T 30-501.	
Standards	IEC 62208 EDF CRT 91 C 112 00	
IP degree of protection	IP65 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
Seismic performance Seismic tests 6G conforming to EDF CRT 91 C 112 00		

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	47.0 kg
Package 1 Height	89 cm
Package 1 width	36 cm
Package 1 Length	63 cm

Offer Sustainability

REACh Declaration	
Yes	
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Yes	
Yes	
China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	

Contractual warranty

Warranty	18 months
----------	-----------