

# Product datasheet

Specifications



## TeSys D contactor - 3P(3 NO) - AC-3 - <= 440 V 25 A - 110 V DC coil

Local distributor code: 402772347    LC1D25FL

### Main

|                                             |                                                                                                                                                                                                                                                                                                                            |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                       | TeSys<br>TeSys Deca                                                                                                                                                                                                                                                                                                        |
| Product name                                | TeSys D<br>TeSys Deca                                                                                                                                                                                                                                                                                                      |
| Product or component type                   | Contacteur                                                                                                                                                                                                                                                                                                                 |
| Device short name                           | LC1D                                                                                                                                                                                                                                                                                                                       |
| Contacteur application                      | Resistive load<br>Motor control                                                                                                                                                                                                                                                                                            |
| Utilisation category                        | AC-3<br>AC-1<br>AC-3e                                                                                                                                                                                                                                                                                                      |
| Poles description                           | 3P                                                                                                                                                                                                                                                                                                                         |
| Power pole contact composition              | 3 NO                                                                                                                                                                                                                                                                                                                       |
| [Ue] rated operational voltage              | Power circuit: <= 690 V AC 25...400 Hz<br>Power circuit: <= 300 V DC                                                                                                                                                                                                                                                       |
| [Ie] rated operational current              | 25 A (at <60 °C) at <= 440 V AC AC-3 for power circuit<br>40 A (at <60 °C) at <= 440 V AC AC-1 for power circuit<br>25 A (at <60 °C) at <= 440 V AC AC-3e for power circuit                                                                                                                                                |
| Motor power kW                              | 5.5 kW at 220...230 V AC 50/60 Hz<br>11 kW at 380...400 V AC 50/60 Hz<br>11 kW at 415...440 V AC 50/60 Hz<br>15 kW at 500 V AC 50/60 Hz<br>15 kW at 660...690 V AC 50/60 Hz                                                                                                                                                |
| Motor power HP (UL / CSA)                   | 3 hp at 230/240 V AC 50/60 Hz for 1 phase motors<br>2 hp at 115 V AC 50/60 Hz for 1 phase motors<br>7.5 hp at 230/240 V AC 50/60 Hz for 3 phases motors<br>15 hp at 460/480 V AC 50/60 Hz for 3 phases motors<br>20 hp at 575/600 V AC 50/60 Hz for 3 phases motors<br>7.5 hp at 200/208 V AC 50/60 Hz for 3 phases motors |
| Control circuit type                        | DC low consumption                                                                                                                                                                                                                                                                                                         |
| [Uc] control circuit voltage                | 110 V DC                                                                                                                                                                                                                                                                                                                   |
| Auxiliary contact composition               | 1 NO + 1 NC                                                                                                                                                                                                                                                                                                                |
| [Uimp] rated impulse withstand voltage      | 6 kV conforming to IEC 60947                                                                                                                                                                                                                                                                                               |
| Overvoltage category                        | III                                                                                                                                                                                                                                                                                                                        |
| [Ith] conventional free air thermal current | 10 A (at 60 °C) for signalling circuit<br>40 A (at 60 °C) for power circuit                                                                                                                                                                                                                                                |
| Irms rated making capacity                  | 140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>450 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                     |

|                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated breaking capacity                  | 450 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| [Icw] rated short-time withstand current | 240 A 40 °C - 10 s for power circuit<br>380 A 40 °C - 1 s for power circuit<br>50 A 40 °C - 10 min for power circuit<br>120 A 40 °C - 1 min for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Associated fuse rating                   | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>63 A gG at <= 690 V coordination type 1 for power circuit<br>40 A gG at <= 690 V coordination type 2 for power circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Average impedance                        | 2 mOhm - Ith 40 A 50 Hz for power circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| [Ui] rated insulation voltage            | Power circuit: 690 V conforming to IEC 60947-4-1<br>Power circuit: 600 V CSA certified<br>Power circuit: 600 V UL certified<br>Signalling circuit: 690 V conforming to IEC 60947-1<br>Signalling circuit: 600 V CSA certified<br>Signalling circuit: 600 V UL certified                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Electrical durability                    | 1.65 Mcycles 25 A AC-3 at Ue <= 440 V<br>1.4 Mcycles 40 A AC-1 at Ue <= 440 V<br>1.65 Mcycles 25 A AC-3e at Ue <= 440 V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Power dissipation per pole               | 3.2 W AC-1<br>1.25 W AC-3<br>1.25 W AC-3e                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Front cover                              | With                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Mounting support                         | Rail<br>Plate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Standards                                | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508<br>IEC 60335-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Product certifications                   | BV<br>CSA<br>CCC<br>LROS (Lloyds register of shipping)<br>GOST<br>DNV<br>UL<br>RINA<br>GL<br>UKCA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Connections - terminals                  | Control circuit: screw clamp terminals 1 cable(s) 1...4 mm²flexible without cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...4 mm²flexible without cable end<br>Control circuit: screw clamp terminals 1 cable(s) 1...4 mm²flexible with cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm²flexible with cable end<br>Control circuit: screw clamp terminals 1 cable(s) 1...4 mm²solid without cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...4 mm²solid without cable end<br>Power circuit: screw clamp terminals 1 cable(s) 2.5...10 mm²flexible without cable end<br>Power circuit: screw clamp terminals 2 cable(s) 2.5...10 mm²flexible without cable end<br>Power circuit: screw clamp terminals 1 cable(s) 1...10 mm²flexible with cable end<br>Power circuit: screw clamp terminals 2 cable(s) 1.5...6 mm²flexible with cable end<br>Power circuit: screw clamp terminals 1 cable(s) 1.5...10 mm²solid without cable end<br>Power circuit: screw clamp terminals 2 cable(s) 2.5...10 mm²solid without cable end |
| Tightening torque                        | Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2<br>Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver pozidriv No 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Operating time                           | 65.45...88.55 ms closing<br>20...30 ms opening                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Safety reliability level                 | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Mechanical durability                    | 30 Mcycles                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Maximum operating rate                   | 3600 cyc/h 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Complementary                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Coil technology                          | Built-in bidirectional peak limiting diode suppressor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

|                                |                                                                                                                                 |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Control circuit voltage limits | 0.1...0.3 Uc (-40...70 °C):drop-out DC<br>0.8...1.25 Uc (-40...60 °C):operational DC<br>1...1.25 Uc (60...70 °C):operational DC |
| Time constant                  | 40 ms                                                                                                                           |
| Inrush power in W              | 2.4 W (at 20 °C)                                                                                                                |
| Hold-in power consumption in W | 2.4 W at 20 °C                                                                                                                  |
| Auxiliary contacts type        | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1        |
| Signalling circuit frequency   | 25...400 Hz                                                                                                                     |
| Minimum switching current      | 5 mA for signalling circuit                                                                                                     |
| Minimum switching voltage      | 17 V for signalling circuit                                                                                                     |
| Non-overlap time               | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact                         |
| Insulation resistance          | > 10 MOhm for signalling circuit                                                                                                |

## Environment

|                                       |                                                                                                                                                                                   |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection               | IP20 front face conforming to IEC 60529                                                                                                                                           |
| Climatic withstand                    | conforming to IACS E10<br>conforming to IEC 60947-1 Annex Q category D                                                                                                            |
| Protective treatment                  | TH conforming to IEC 60068-2-30                                                                                                                                                   |
| Pollution degree                      | 3                                                                                                                                                                                 |
| Ambient air temperature for operation | -40...60 °C<br>60...70 °C with derating                                                                                                                                           |
| Ambient air temperature for storage   | -60...80 °C                                                                                                                                                                       |
| Operating altitude                    | 0...3000 m                                                                                                                                                                        |
| Fire resistance                       | 850 °C conforming to IEC 60695-2-1                                                                                                                                                |
| Mechanical robustness                 | Vibrations contactor open: 2 Gn, 5...300 Hz<br>Vibrations contactor closed: 4 Gn, 5...300 Hz<br>Shocks contactor closed: 15 Gn for 11 ms<br>Shocks contactor open: 8 Gn for 11 ms |
| Height                                | 85 mm                                                                                                                                                                             |
| Width                                 | 45 mm                                                                                                                                                                             |
| Depth                                 | 101 mm                                                                                                                                                                            |
| Net weight                            | 0.53 kg                                                                                                                                                                           |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 565.0 g  |
| Package 1 Height             | 4.9 cm   |
| Package 1 width              | 11.1 cm  |
| Package 1 Length             | 8.9 cm   |
| Unit Type of Package 2       | S02      |
| Number of Units in Package 2 | 15       |
| Package 2 Weight             | 8.786 kg |
| Package 2 Height             | 15 cm    |
| Package 2 width              | 30 cm    |

|                  |       |
|------------------|-------|
| Package 2 Length | 40 cm |
|------------------|-------|


### Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| Toxic heavy metal free     | Yes                                                                                                                         |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                 |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free                   | Yes                                                                                                                         |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions



(1) Minimum electrical clearance

| LC1 |                                    | D25...D38 | D183...D323 |
|-----|------------------------------------|-----------|-------------|
| b   |                                    | 85        | 99          |
| c   | without cover or add-on blocks     | 99        | 99          |
|     | with cover, without add-on blocks  | 101       | 101         |
| c1  | with LAD N or C (2 or 4 contacts)  | 132       | 132         |
| c2  | with LA6 DK10                      | 144       | 144         |
| c3  | with LAD T, R, S                   | 152       | 152         |
|     | with LAD T, R, S and sealing cover | 156       | 156         |

Wiring

