wall-mounting encl. polyester monobloc IP66 H647xW436xD250mm+metal mount.plate

Local distributor code: 403422764 NSYPLM64PG

VI	a	ı	r

Range	Thalassa
Product name	Thalassa PLM
Device short name	PLM
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	647 mm
Nominal width	436 mm
Nominal depth	250 mm
Enclosure mounting	Wall mounted
Device composition	1 body 1 door 1 mounting plate 2 lock
Door type	Plain
Lock type	3 mm double-bar lock

Complementary

2
Plain steel
Front
Door by hinges Mounting plate by fixing element
Polyester reinforced with fibreglass
Grey (RAL 7035)
IEC 62208 NEMA classification 13 NEMA classification 4X
UL
Class II

Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

Fire resistance	960 °C conforming to IEC 62208		
mbient air temperature for peration	-4080 °C		
Packing Units			
Init Type of Package 1	PCE		
umber of Units in Package 1	1		
ackage 1 Weight	13.1 kg		
Package 1 Height	45 cm		
Package 1 width	27.5 cm		
Package 1 Length	68 cm		
Jnit Type of Package 2	CAR		
Number of Units in Package 2	1		
Package 2 Weight	13.1 kg		
Package 2 Height	71.5 cm		
Package 2 width	27.5 cm		
ackage 2 Length	46 cm		
Offer Sustainability			
Sustainable offer status	Green Premium product		
REACh Regulation	REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information		

Warranty	18 months		
----------	-----------	--	--