# **Product datasheet**

Specifications



Control window IP 55 with aluminum frame and 3 mm acrylic window 500 x 400 mm

NSYCW54

#### Main

Range	Spacial
Accessory / separate part category	Installation accessory
Product or component type	Window
For enclosure nominal dimensions	-
Range compatibility	Spacial S3D Spacial CRN
Mounting location	Installation on door or panel
Device composition	2 hinge 1 lock 1 fixings and drilling template 1 frame with window
Material	Transparent acrylic aluminium
Lock type	Closure by lock
Number of locks	1
Key number	2233X

### Complementary

Height	500 mm
Width	400 mm
Depth	77 mm
Type of installation	Indoor installation

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	4.012 kg
Package 1 Height	56 cm
Package 1 width	44 cm
Package 1 Length	12 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

## **Contractual warranty**

Warranty	18 months	
----------	-----------	--