

# Product datasheet

Specifications



Polyester glassreinf. plinth for encl.  
PLA(T)123 front opening IP44-IK10  
RAL7035

NSYZA2123G

## Main

Range	Thalassa
Accessory / separate part category	Enclosure accessory
Product or component type	Plinth
Anwendung	Multi-purpose
Nennmaße des Gehäuses	-
Device composition	fixing elements 2 front panel 2 side part
Range compatibility	Thalassa PLA

## Complementary

Fixing mode	By screws - on side parts location
Colour	Plinth: grey (RAL 7035)
Height	200 mm
Width	1244 mm
Depth	250 mm

## Environment

IP degree of protection	IP44
IK degree of protection	IK10

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	8.9 kg
Package 1 Height	16 cm
Package 1 width	21.5 cm
Package 1 Length	127 cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

---

<b>EU RoHS Directive</b>	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information

---

## **Contractual warranty**

---

<b>Warranty</b>	18 months
-----------------	-----------

---