

Product datasheet

Specifications



Test position contact CT - for MTZ

LV833752

Main

Range	Masterpact
Device short name	CT
Product or component type	Auxiliary contact
Device application	Control
Range compatibility	MasterPact MTZ1 circuit breaker MasterPact MTZ2 circuit breaker MasterPact MTZ3 circuit breaker
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
Auxiliary contacts operation	Test position
Mounting mode	Drawout
[Ie] rated operational current	AC-12: 6 A at 690 V AC 50/60 Hz AC-12: 8 A at 240 V AC 50/60 Hz AC-12: 8 A at 380 V AC 50/60 Hz AC-12: 8 A at 480 V AC 50/60 Hz DC-12: 0.8 A at 125 V DC DC-12: 2.5 A at 24/48 V DC DC-12: 0.3 A at 150 V DC
Minimum load	100 mA at 24 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.018 kg
Package 1 Height	0.9 cm
Package 1 width	4.2 cm
Package 1 Length	4.2 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes

RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Contractual warranty	
Warranty	18 months