

Product datasheet

Specifications



Micrologic 5.0 X control unit, for Masterpact MTZ2/MTZ3 circuit breakers, drawout, LSI protections

LV848499

Main

Range	Masterpact
Device short name	Micrologic 5.0 X
Product or component type	Control unit
Device application	Equipment protection, monitoring and control
Circuit breaker application	Distribution IEC standard
Range compatibility	MasterPact MTZ2 H2 corrosion protection circuit breaker MasterPact MTZ2 H10 circuit breaker MasterPact MTZ2 circuit breaker MasterPact MTZ3 circuit breaker
Poles	3P 4P
Protected poles	3P 3d 4P 3d + N/2 4P 4d 4P 3d + OSN 4P 3d
[Ue] rated operational voltage	690 V AC, +/- 10 %
Network type	AC
Network frequency	50/60 Hz
Trip unit technology	Electronic
Trip unit protection functions	LSI
Protection type	Overload protection (long time) conforming to ANSI 49 Instantaneous short-circuit protection conforming to ANSI 50 Short time short-circuit protection conforming to ANSI 51
Trip unit rating	5000 A 1600 A 2500 A 3200 A 1250 A 400 A 4000 A 800 A 1000 A 630 A 2000 A 6300 A

Complementary

Mounting mode	Drawout
[Ir] long time pick-up adjustment range	0.4...1 x In adjustable in step of 1 A

Long time delay adjustment type	Adjustable in step of 0.5 s
[Tr] long-time delay adjustment range	12.5...600 s at 1.5 x Ir 0.5...24 s at 6 x Ir 0.7...16.6 s at 7.2 x Ir
Thermal memory	Yes
[Isd] short-time pick-up adjustment range	1.5...10 x Ir adjustable in step of 0.5 x Ir with embedded HMI 1.5...10 x Ir adjustable in step of 0.1 x Ir with Ecoreach software or MasterPact MTZ mobile app
Short-time delay adjustment type	Adjustable
[Tsd] short-time delay adjustment range	0.1...0.4 s I ² t=on 0...0.4 s I ² t=off
Instantaneous pick-up adjustment type li	Adjustable
[li] instantaneous pick-up adjustment range	2...15 x In adjustable in step of 0.5 x In with embedded HMI 2...15 x In adjustable in step of 0.1 x In with Ecoreach software or MasterPact MTZ mobile app li enable on/off
[Li mode] instantaneous delay adjustment range	0 ms in fast 20 ms in standard
Zone selective interlocking ZSI	With
Network and machine diagnosis type	System (HMI) health state overview: circuit breaker health state standard) Contacts state: circuit breaker health state standard) Micrologic service life: circuit breaker health state standard) Tripping cause indication: circuit breaker tripping cause standard) Identification card: diagnostic data standard) Configured alarms synthesis: diagnostic data standard) Monitored function: diagnostic data standard) Operation: diagnostic data standard) Micrologic test: test standard) Protection test: test standard) Selectivity test: test standard) Trip context information: crisis management standard) Operation: advanced diagnostic standard) Breaker service life: circuit breaker health state standard)
Type of measurement	Power meter
Energy management	Measurement ,active, reactive and apparent energy (standard) Measurement ,electrical network (standard) Measurement ,energy (standard)
Metering type	Current I1, I2, I3, In, Ig: maximum standard) Average voltage Vavg standard) Active power P, P1, P2, P3 standard) Reactive power Q, Q1, Q2, Q3 standard) Apparent power S, S1, S2, S3 standard) Power factor standard) Frequency standard) Total current harmonic distortion THD (I): inst, avg, avg min, avg max fundamental voltage standard) Total current harmonic distortion THD (I): inst, avg, avg min, avg max RMS voltage standard) Voltage V21, V32, V13, V1, V2, V3: instantaneous standard) Voltage V21, V32, V13, V1, V2, V3: minimum standard) Voltage V21, V32, V13, V1, V2, V3: maximum standard) Total voltage harmonic distortion THD (V): inst, avg, avg min, avg max fundamental voltage standard) Total voltage harmonic distortion THD (V): inst, avg, avg min, avg max RMS voltage standard) Demand current I1, I2, I3, In, lavg standard) Demand power P, Q, S standard)
Measurement voltage	145.6...828 V AC 50/60 Hz per phase
Frequency measurement range	45...250 Hz
Measurement accuracy	Power factor: +/- 1 % Active energy Ep IN/OUT/tot: +/- 1 % - 10...10 GWh Reactive energy Ep IN/OUT/tot: +/- 2 % - 10...10 GVARh Apparent energy Es IN/OUT/tot: +/- 1 % - 10...10 GVAh Unbalance current: +/- 0.5 % Frequency: +/- 0.005 Hz Voltage V21, V32, V13, VLLavg: +/- 0.5 % 208...690 x 1.2 V Voltage V21, V32, V13, VLNavg: +/- 0.5 % 120...400 x 1.2 V Apparent power S, S1, S2, S3, Sdemand: +/- 1 % Active power P, P1, P2, P3, Pdemand: +/- 1 % Reactive power Q, Q1, Q2, Q3, Qdemand: +/- 2 % Current I1, I2, I3, lavg, Idemand for MTZ1: +/- 0.5 % 40...1600 x 1.2 A Current I1, I2, I3, lavg, Idemand for MTZ2: +/- 0.5 % 40...4000 x 1.2 A Current I1, I2, I3, lavg, Idemand for MTZ3: +/- 0.5 % 80...6300 x 1.2 A
Accuracy class	Class 5: total current harmonic distortion THD (I) Class 0.5: unbalance voltage

	Class 1: active and reactive energy by pulse counting (+/- W.h, +/- VAR.h) Class 2: total voltage harmonic distortion THD (V)
Display type	LCD display - 128 x 96 pixels
Communication port protocol	Bluetooth 4.0 LE peer to peer 30 kbit/s NFC peer to peer conforming to ISO 15963 USB peer to peer 115 kbauds
Data recording	Event logs Data logs Time stamping Alarm logs Min/max of instantaneous values Maintenance logs

Environment

Standards	EN/IEC 60947-2 EN/IEC 60947-1 EN/IEC 60255-1 EN/IEC 60092-202 EN/IEC 61010-1
Mounting location	Indoor use only
Environmental characteristic	Wet location not approved for use conforming to IEC 61010-1
Electromagnetic compatibility	Electrostatic discharge immunity test conforming to IEC 61000-4-2 Susceptibility to electromagnetic fields conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 1.2/50 µs shock waves immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Conducted and radiated emissions A conforming to CISPR 22
Overvoltage category	IV conforming to IEC 61010-1
Measurement category	Category IV conforming to IEC 61010-2-30
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25...70 °C (operating) -35 °C (for start-up of product)
Relative humidity	95 % at 55 °C conforming to IEC 60068-2-30
Operating altitude	<= 2000 m without derating <= 4000 m with operational voltage derating 600 V AC <= 5000 m with operational voltage derating 560 V AC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	369.0 g
Package 1 Height	6.7 cm
Package 1 width	7.9 cm
Package 1 Length	21.6 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

PVC free	Yes
Halogen content performance	Halogen free plastic parts product
Contractual warranty	
Warranty	18 months