

Product datasheet

Specifications



motor mechanism MCH 200 to 240 V AC

47894

Main

Range of product	MasterPact NW
Range	Masterpact
Device short name	Gear motor MCH
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	MasterPact NW circuit breaker EasyPact MVS circuit breaker
[Uc] control circuit voltage	200/240 V AC 50/60 Hz

Complementary

Control type	Motor mechanism
Maximum charging time	4 s
Maximum operating frequency	<= 3 cycles per minute
Threshold tripping voltage	0.85...1.1 Un
Maximum power consumption in VA	180 VA
Accessory / separate part category	Spare parts for MasterPact NW

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.88 kg
Package 1 Height	12.5 cm
Package 1 width	13.5 cm
Package 1 Length	23.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Weight	11.9 kg
Package 2 Height	30 cm
Package 2 width	30 cm

Package 2 Length	40 cm
Package 3 Height	50 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

Contractual warranty

Warranty	18 months
----------	-----------