Room Thermostat, Wiser

Local distributor code: 407909788 WN704R0S0902

Main

Range of product	Wiser	
Range	Wiser	
Product or component type	Thermostat	
Provided equipment	2 x batteries 1 x wall-mount bracket 1 x stand	
Battery type	AA alkaline 1.5 V	
Colour tint	White (RAL 9003)	

Complementary			
Technology type	Electronic		
Device application	Room		
Display type	Colour TFT LCD 2.4 inch		
Function available	With humidity sensor		
Information displayed	Room temperature Relative humidity Temperature set point Battery level Boost status Heating symbol Signal status		
Communication network type	Wireless Zigbee (2.4 GHz), 2.5 mW		
Maximum radio power	13 dBm (20 mW)		
[Sd] sensing range	030 m		
Control type	2 touch type, for temperature adjustment 1 touch type, for temperature boost by mobile application remote control		
Local signalling	LED flashing red for no signal disconnection LED flashing red for low battery indication		
Name of test	Ball pressure 75 °C		
Software class	Class A		
Mounting location	wall mounting		
Mounting support	Wall bracket Stand		
Width	76 mm		

Relative humidity 2596 1598 1598	°C 55 °C
Environment Ambient air temperature for operation Ambient air temperature for storage Temperature setting range 535 0.5 °C Relative humidity 2599 1599 1599 1599 1599 1599 1599 1599 1799 1899 1990 Padgree of protection IP20 Standards EN 60 EN	°C per step 0 % operating
Ambient air temperature for operation Ambient air temperature for storage Temperature setting range 535 0.5 °C Relative humidity 2590 1590 1590 1590 Packing Units Unit Type of Package 1 Package 1 Weight Package 1 Height 545 Package 1 Height -105 -1	°C per step 0 % operating
Ambient air temperature for storage Temperature setting range 535 0.5 °C Relative humidity 2591 1593 IP degree of protection IP20 Standards EN 60	°C per step 0 % operating
storage Temperature setting range 535 0.5 °C Relative humidity 2590 15	°C per step 0 % operating
Relative humidity 259 159 159 119 119 129 15	per step 0 % operating
IP degree of protection IP20 Standards EN 60 EN 60 EN 60 EN 60 EN 30 Directives 2014/5 2006/6 Packing Units Unit Type of Package 1 Package 1 Weight Package 1 Height 5.6 cm	
Standards EN 60 EN 60 EN 60 EN 60 EN 30 Directives 2014/5 2006/6 Packing Units Unit Type of Package 1 PCE Number of Units in Package 1 Package 1 Weight 156.4 Package 1 Height 5.6 cm	o // storage
EN 60 EN 60 EN 60 EN 30 Directives 2014/5 2006/6 Packing Units Unit Type of Package 1 PCE Number of Units in Package 1 Package 1 Weight 156.4 Package 1 Height 5.6 cm	
Packing Units Unit Type of Package 1 PCE Number of Units in Package 1 1 Package 1 Weight 156.4 Package 1 Height 5.6 cm	730-2-7 730-2-9
Unit Type of Package 1 PCE Number of Units in Package 1 1 Package 1 Weight 156.4 Package 1 Height 5.6 cm	53/EU - radio equipment directive 66/EC - battery directive
Number of Units in Package 1 1 Package 1 Weight 156.4 Package 1 Height 5.6 cm	
Package 1 Weight 156.4 Package 1 Height 5.6 cm	
Package 1 Height 5.6 cm	
	g
Package 1 width 8.2 cm	١
	١
Package 1 Length 8.4 cm	١
Unit Type of Package 2 PAM	
Number of Units in Package 2 200	
Package 2 Weight 51.28	kg
Package 2 Height 115 cm	n
Package 2 width 100 cm	n
Package 2 Length 120 cm	n
Offer Sustainability	
·	Premium product
REACh Regulation REAC	h Declaration
REACh free of SVHC Yes	
EU RoHS Directive Comp	oliant HS Declaration
Mercury free Yes	
RoHS exemption information Yes	
•	RoHS declaration
Environmental Disclosure Produc	uct out of China RoHS scope. Substance declaration for your information
Circularity Profile End of	ct Environmental Profile
WEEE The prince never	

Contractual warranty

Warranty	18 months
warranty	10 1110111115