

Product datasheet

Specifications



wireless and battery less handy box,
1 simple action button

Local distributor code: 409066991 ZBRM21A0

Main

Range of product	Harmony XB5R
Product or component type	Wireless and batteryless transmitter
Device short name	XB5R
Contact operation	1 simple action push-button
Bezel material	Plastic
Fixing collar material	Plastic
Mounting diameter	22 mm

Complementary

Kit composition	1 handy box 1 transmitter 1 set of caps 1 push-button head diameter: 22 mm 1 fixing collars
Shape of signaling unit head	Round
Type of operator	spring return push-button with transmitter
Operator profile	Flush
Operator additional information	Set of caps
Net weight	0.15 kg
Mechanical durability	1000000 cycles
Operating travel	4.3 mm (total travel)
Operating force	25 N C/O changing electrical state
Shock resistance	25 gn (duration = 6 ms) for 6000 shocks conforming to IEC 60068-2-27 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27
Mechanical robustness	Free fall resistance 1000 mm conforming to EN/IEC 60068-2-32
Communication port protocol	Zigbee green power at 2.4 GHz
Maximum sensing distance	100 m in free field 25 m transmitter in the handy box and receiver in a metal enclosure 300 m transmitter in the handy box, receiver in metal enclosure and use relay-antenna
Acquisition time	2 ms
Response time	< 2 ms
Emission power	3 mW

Environment

Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...55 °C
IP degree of protection	IP65 (front face) conforming to IEC 60529 IP65 (front face) conforming to UL Type 12
IK degree of protection	IK03 conforming to IEC 50102
Relative humidity	95 % at 70 °C without condensation
Vibration resistance	5 gn (f= 11...500 Hz) conforming to IEC 60068-2-6 +/- 10 mm (f= 2...11 Hz) conforming to IEC 60068-2-6
Electromagnetic compatibility	Electrostatic discharge immunity test - test level: 8 kV (in free air (in insulating parts)) conforming to IEC 61000-4-2 Electrostatic discharge immunity test - test level: 4 kV (on contact (on metal parts)) conforming to IEC 61000-4-2 Susceptibility to electromagnetic fields - test level: 20 V/m (80...3000 MHz) conforming to IEC 61000-4-3 Susceptibility to electromagnetic fields - test level: 6 V/m (3000...6000 MHz, distance = 20 m) conforming to IEC 61000-4-3
Radio agreement	RSS conforming to UL 508 ARIB T66 conforming to CSA C22.2 No 14 ICASA ANATEL FCC
Standards	EN/IEC 60947-1 UL 508 CSA C22.2 No 14 EN/IEC 60947-5-1
Product certifications	EAC BT 2006/95/EC C-Tick UL CSA CCC
Directives	1999/5/EC - R&TTE directive 2004/108/EC - electromagnetic compatibility

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	187.0 g
Package 1 Height	6.5 cm
Package 1 width	6.5 cm
Package 1 Length	16.3 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions

Wireless and Batteryless Pushbutton

Plastic Mobile Box for Mobile or Fix Use - 1 Function

