

trip unit TM160D for ComPacT NSX 160/250 circuit breakers, thermal magnetic, rating 160 A, 4 poles 4d

C164TM160

Range	ComPacT new generation
Range of product	ComPacT NSX100250 new generation
Product or component type	Trip unit
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Range compatibility	ComPacT new generation NSX160
Device application	Distribution
Poles description	4P
Protected poles description	4t
Neutral position	Left
Trip unit protection functions	Ц
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rating	160 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Fixed

Complementary

Long-time pick-up adjustment type Ir (thermal protection)	Adjustable
[Ir] long-time protection pick-up adjustment range	0.71 x ln
Long-time protection delay adjustment type tr	Fixed
[Tr] long-time protection delay adjustment range	120400 s at 1.5 x ln 15 s at 6 x lr
Short-time protection pick-up adjustment type Isd	Fixed
[Isd] Short-time protection pick- up adjustment range	1250 A

Short-time protection delay	Fixed
adjustment type tsd	
Earth-leakage protection	Without
Neutral protection settings	1 x lr (4t)
Environment	
Standards	UL 508 EN/IEC 60947-2
Product certifications	EAC Marine CCC
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-5085 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	502.0 g
Package 1 Height	6.7 cm
Package 1 width	9.8 cm
Package 1 Length	14.8 cm
Unit Type of Package 2	S03

Package 1 Height	6.7 cm
Package 1 width	9.8 cm
Package 1 Length	14.8 cm
Unit Type of Package 2	S03
Number of Units in Package 2	23
Package 2 Weight	11.924 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Mercury free	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
REACh Regulation	REACh Declaration

Contractual warranty