



Main

Circuit breaker application	Distribution
Range	Acti 9
Product name	iKQE RCBO
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Poles description	1P + Ns
[In] rated current	25 A
Curve code	B
Earth-leakage sensitivity	30 mA
Breaking capacity	10 kA Icn at 150...230 V AC 50 Hz

Complementary

Network type	AC
Network frequency	50 Hz
[Ue] rated operational voltage	150...230 V AC 50 Hz
Trip unit technology	Thermal-magnetic
Earth-leakage protection class	Type A
Electrical insulation class	Class III
Limitation class	3
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	YES
Colour	White
Provision for padlocking	Padlockable
Locking options description	ON/OFF locking facilities
Connections - terminals	Screw clamp terminal 1...16 mm ²
Earth-leakage protection	Integrated
Targeted country	UK

Environment

Standards	BS EN 61009
-----------	-------------

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty

18 months
