

JC17072

Rechargeable Table Lamps

Round rechargeable lamp with charging base 2W IP54 3000K 168lm White

Features & Benefits

- Ideal for domestic applications, no electrician required
- This portable touch dimmable lamp allows for flexible illumination
- 6-8 hrs charge time, with up to 10 hrs run time at 100% light output
- The docking station is ideal for charging and convenient portability for use anywhere around the home
- Uses Lithium-ion batteries, increased charge and discharge cycles, for longer life span
- 3000K colour temperature to match the Architectural Exterior Range
- IP54 rating, suitable for exterior use



General Information

Product Group	Architectural Exterior
Product Range	Rechargeable
IK Rating	IP54
Color Finish	White
Product Shape	Conical
Overall Dimensions	280 x 110 Ø
Light Source	LED
Light Source Features	Warm White
Additional Information	UK USB Plug Adapter/ 1.2m USB charging lead pre-wired to docking station.
Origin of manufacturer	China
Warranty	2 years standard warranty extends to 3 years when registered within the first year of purchase (2 years on batteries) (See Website for terms and conditions)
LED Manufacturer/Type	Philips 3014

Electrical

Voltage Rating	220-240V~
Operating Frequency Hz	50/60Hz

Luminaire Circuit Wattage	2
Class	Class II Plug Adapter, Class III luminaire
Battery Data	
Battery Specification	2 * 18650 3.7V 2200mAh Lithium-ion
Battery Type	Lithium ion
Nominal Battery Current	4.4 Amp
Charge Current	1 Amp
Recharge Time	(Mains USB)6-8 hrs
Battery run time	Running time(Light @Full Power) 10hrs.
Performance Data	
LED Life (Hours)	36000
Hours life stated is an indication of expected L70 chip and light output calculations whenoperating in optimum conditions. Product warranty period supports the full productduring the term given. The L70 hours expectancy is not correlated with the full productwarranty term, nor is it a representation of lumen depreciation during the warrantyperiod.	
Energy Rating	This product contains a light source of energy efficiency class E
Actual Lumen Output	190
Lumens Per Circuit Watt	95
Standard Deviation Colour Matching - SDCM	>5
Color Rendering Index	80-89
CRI: Ra	84
Correlated Color Temperature	3000K
LOR (Light Output Ratio) %	100
Photometry Available	Yes
Construction	
Primary Material	Aluminium
Lens	Clear PC
Heat Sink	Aluminium
Seal Material	Silicon
Packaging	
Quantity Per Outer Carton	12
Outer carton(L)- cm	53.50
Outer carton(W)- cm	40.5
Outer carton(H)- cm	37.0
Outer carton Net weight- kg	5.76kg
Outer carton Gross weight- kg	10.80kg
Product Bar Code EAN-13 Number	5052544109430
Outer carton Bar Code ITF-14 Number	15052544109437

Standards & Approvals

Manufactured In Accordance To
CE Marked
UKCA Marked
Date code/Purchase order No.
WEEE Symbol
Certificate Of Conformity
Accredited Members

BS EN 60598-2015
Yes
Yes
Yes
Yes
Yes, available on request
LIA, ISO9001:2015, ISO14001:2015



JCC Lighting LTD Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex PO22 9TS
Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk
Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 114 [06/07/2022]