



MASTER LED candles and lusters

MASTER LEDcandle DT 6-40W E14 BA38 CL

Delivering incandescent-like sparkling light effects, MASTER LED candles and lusters are ideal for general and decorative lighting in the hospitality industry as well as in home environments. Mounted in full view in chandeliers, wall scones or modern luminaires, the clear or frosted glass candles and lusters fit all existing fixtures with an E14, B15, B22 or E27 socket, and enhance the aesthetic appeal of the chandelier or luminaire both when on and off, with their unique, eye-catching lens design. They produce a beautiful sparkling warm light that delivers huge energy savings and minimizes maintenance cost.

Product data

General Information		Operating and Electrical	
Cap-Base	E14 [E14]	Input Frequency	50 to 60 Hz
EU RoHS compliant	Yes	Power (Nom)	6 W
Nominal Lifetime (Nom)	25000 h	Lamp Current (Nom)	35 mA
Switching Cycle	50000X	Wattage Equivalent	40 W
Technical Type	6-40W	Starting Time (Nom)	0.5 s
Light Technical		Warm Up Time to 60% Light (Nom)	0.5 s
Color Code	822-827 [tunable warm white]	Power Factor (Nom)	0.7
Luminous Flux (Nom)	470 lm	Voltage (Nom)	220-240 V
Color Designation	Warm White (WW)	Temperature	
Correlated Color Temperature (Nom)	- K	T-Case Maximum (Nom)	95 °C
Luminous Efficacy (rated) (Nom)	75 lm/W	Controls and Dimming	
Color Consistency	<6	Dimmable	Yes
Color Rendering Index (Nom)	80		
LLMF At End Of Nominal Lifetime (Nom)	70 %		

MASTER LED candles and lusters

Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	BA38
Approval and Application	
Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	6 kWh
Product Data	
Full product code	871869645354400


Dimensional drawing



Product	D	C
MASTER LEDcandle DT 6-40W E14 BA38 CL	38 mm	129 mm

Candle BA38 220-240V 6W-40W 2700K E14 DT

Photometric data



SDLD_LEDCL_0030-Light distribution diagram

MASTER LED candles and lusters

