

**PHILIPS****Lighting**

# CorePro LEDspot LV

## CorePro LED spot ND 5-35W MR16 840 36D

CorePro LEDspots are a perfect fit for spot lighting and deliver warm halogen-like light. They are compatible with most existing fixtures with MR16 GU5.3 holders and are designed as a retrofit replacement for halogen or incandescent spots. LEDlamps deliver huge energy savings and minimize maintenance cost.

### Product data


General Information	
Cap base	GU5.3 [ GU5.3]
EU RoHS compliant	Yes
Nominal lifetime (nom.)	15000 h
Switching cycle	50,000X
Technical type	5-35W
Light Technical	
Colour Code	840 [ CCT of 4,000 K]
Beam Angle (Nom)	36 °
Luminous flux (nom.)	390 lm
Luminous intensity (nom.)	650 cd
Colour designation	Cool White (CW)
Correlated Colour Temperature (Nom)	4000 K
Luminous efficacy (rated) (nom.)	78.00 lm/W
Colour consistency	<6
Colour rendering index (nom.)	80
LLMF at end of nominal lifetime (nom.)	70 %
Luminous flux in 90° cone (rated)	390 lm
Operating and Electrical	
Input frequency	- Hz
Power (Rated) (Nom)	5 W
Product Data	
Full product code	871869671065400
Order product name	CorePro LED spot ND 5-35W MR16 840 36D
Temperature	
T-Case maximum (nom.)	82 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb shape	MR16 [ 2inch/50mm]
Approval and Application	
Suitable for accent lighting	Yes
Energy consumption kWh/1,000 hours	6 kWh

# CorePro LEDspot LV

EAN/UPC – product	8718696710654
Order code	71065400
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10

SAP material	929001344502
SAP net weight (piece)	0.045 kg



## Dimensional drawing



MR16 12V ACV 4.7-35W 450lm 36D 4000K ND


Product	D	C
CorePro LED spot ND 5-35W MR16 840 36D	51 mm	46 mm

## Photometric data



CorePro LEDspotLV 35W GU5-3 840 36D



CorePro LEDspotLV 35W GU5-3 840 36D



CorePro LEDspotLV 35W GU5-3 840 36D

## CorePro LEDspot LV

### Lifetime



CorePro LEDspotLV 20W GU5-3 827 36D

CorePro LEDspotLV 20W GU5-3 827 36D

