



# MASTER VALUE LEDspot MV



# MASTERLEDspot VLE D 6.2-80W GU10 927 36D UK

Delivering a warm, halogen-like accent beam, the MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it achieves more natural colours, creating cosy and comfortable ambience for residential and hospitality projects, and emphasising the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. The MASTER VALUE also offers more energy savings than normal LED spots.

#### **Warnings and Safety**

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

#### **Product data**

General information	
Cap base	GU10 [ GU10]
EU RoHS compliant	Yes
Nominal lifetime (nom.)	25000 h
Switching cycle	50,000X
Light technical	
Colour Code	927 [ CCT of 2,700 K]
Beam Angle (Nom)	36 °
Luminous flux (nom.)	575 lm

Luminous intensity (nom.)	850 cd	
Colour designation	Warm white (WW)	
Correlated Colour Temperature (Nom)	2700 K	
Luminous efficacy (rated) (nom.)	92.00 lm/W	
Colour consistency	<6	
Colour rendering index (nom.)	90	
LLMF at end of nominal lifetime (nom.) 70 %		
Luminous flux in 90° cone (rated)	575 lm	


Datasheet, 2022, July 28 data subject to change

## **MASTER VALUE LEDspot MV**

Operating and electrical	
Input frequency	50 to 60 Hz
Power (Rated) (Nom)	6.2 W
Lamp current (nom.)	33 mA
Wattage equivalent	80 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light (nom.)	0.5 s
Power factor (nom.)	0.88
Voltage (Nom)	220-240 V
Temperature	
T-Case maximum (nom.)	80 °C
Controls and dimming	
Dimmable	Yes
Mechanical and housing	
Bulb shape	PAR16 [ PAR 2 inch]

Approval and application	
Energy Efficiency Class	F
Suitable for accent lighting	Yes
Energy consumption kWh/1,000 hours	7 kWh
	391905
Product data	
Full product code	871869967541701
Order product name	MASTERLEDspot VLE D 6.2-80W GU10 927 36D
	UK
EAN/UPC – product	8718699675417
Order code	67541701
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
SAP material	929002059599
Copy Net Weight (Piece)	0.038 kg


#### Dimensional drawing




MASTERLEDspot VLE D 6.2-80W GU10 927 36D UK



#### Photometric data




Light Distribution Diagram



Spectral Power Distribution Colour

### **MASTER VALUE LEDspot MV**


#### Photometric data




Calculus Photographics 4.5 Philips Lighting B.V. Rigot IV

Accent Lighting Spots

#### Lifetime





25K LMP 25K LED



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.