



MASTER VALUE LEDspot MV



MASTERLEDspot VLE D 6.2-80W GU10 965 36D UK

Delivering a warm, halogen-like accent beam, the MASTER VALUE is a perfect fit for spot lighting. Thanks to its high CRI, it achieves more natural colours, creating cosy and comfortable ambience for residential and hospitality projects, and emphasising the beauty of merchandise in retail. These LED spots MV GU10 have the familiar look and feel of spot lamps, keeping the classic beauty of glass spots and adding the strong performance of LED technology. The dimming function enables you to create the atmosphere you desire, and it works with broad selection of dimmers. The MASTER VALUE also offers more energy savings than normal LED spots.

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights


Product data

General information			
Cap base	GU10 [GU10]	Luminous intensity (nom.)	850 cd
EU RoHS compliant	Yes	Colour designation	Cool Daylight
Nominal lifetime (nom.)	25000 h	Correlated Colour Temperature (Nom)	6500 K
Switching cycle	50,000X	Luminous efficacy (rated) (nom.)	92.00 lm/W
Light technical		Colour consistency	<6
Colour Code	965 [CCT of 6,500 K]	Colour rendering index (nom.)	90
Beam Angle (Nom)	36 °	LLMF at end of nominal lifetime (nom.)	70 %
Luminous flux (nom.)	575 lm	Luminous flux in 90° cone (rated)	575 lm

MASTER VALUE LEDspot MV


Operating and electrical	
Input frequency	50 to 60 Hz
Power (Rated) (Nom)	6.2 W
Lamp current (nom.)	33 mA
Wattage equivalent	80 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light (nom.)	0.5 s
Power factor (nom.)	0.88
Voltage (Nom)	220-240 V
Temperature	
T-Case maximum (nom.)	80 °C
Controls and dimming	
Dimmable	Yes
Mechanical and housing	
Bulb shape	PAR16 [PAR 2 inch]

Dimensional drawing



MASTERLEDspot VLE D 6.2-80W GU10 965 36D UK


Photometric data



Spectral Power Distribution Colour

Approval and application	
Energy Efficiency Class	F
Suitable for accent lighting	Yes
Energy consumption kWh/1,000 hours	7 kWh
	391916
Product data	
Full product code	871869970607401
Order product name	MASTERLEDspot VLE D 6.2-80W GU10 965 36D UK
EAN/UPC – product	8718699706074
Order code	70607401
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
SAP material	929002209999
Copy Net Weight (Piece)	0.038 kg


Product	D	C
MASTERLEDspot VLE D 6.2-80W GU10 965 36D UK	50 mm	54 mm



Accent Lighting Spots


MASTER VALUE LEDspot MV

Photometric data




Light Distribution Diagram

Lifetime



25K LMP



25K LED

