



## Main

|                           |                    |
|---------------------------|--------------------|
| Transformer type          | Safety transformer |
| Range                     | Acti 9             |
| Range of product          | Acti 9             |
| Product name              | Acti 9 iTR         |
| Product or component type | Transformer        |
| Device short name         | ITR                |

## Complementary

|                                 |                                              |
|---------------------------------|----------------------------------------------|
| [Ue] rated operational voltage  | 230 V AC 50/60 Hz                            |
| Output voltage                  | 12/24 V: +/-5 % on load<br>14/28 V: off load |
| Output short-circuit protection | Built-in                                     |
| Rated power in VA               | 63 VA                                        |
| Mounting mode                   | Fixed                                        |
| Mounting support                | 35 mm symmetrical DIN rail                   |
| 9 mm pitches                    | 10                                           |
| Height                          | 89 mm                                        |
| Width                           | 90 mm                                        |
| Depth                           | 60 mm                                        |
| Colour                          | White                                        |
| Auxiliary connection terminal   | Tunnel type terminals 4 mm <sup>2</sup>      |

## Environment

|                                       |                                           |
|---------------------------------------|-------------------------------------------|
| Standards                             | IEC 61558-2-6<br>EN 60742<br>EN 61558-2-6 |
| Product certifications                | NF                                        |
| Overvoltage category                  | Class II with terminal shields in option  |
| Ambient air temperature for operation | -20...55 °C                               |
| Ambient air temperature for storage   | -25...80 °C                               |

## Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>                                                                               |
| Toxic heavy metal free     | Yes                                                                                                                         |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                      |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|