

LEXINGTON

LED 3 hour maintained/non-maintained exit box



WITH EURO LEGEND



WITH ISO LEGEND



APPLICATIONS

- Corridors
- Exits
- Escape routes

CONSTRUCTION

- Robust steel body
- White gloss powder coated finish
- Polycarbonate legend panel
- Supplied complete with either EURO legend "DOWN" arrow or ISO legend "UP" arrow (ahead)
- Nickel Cadmium (NiCd) battery (not suitable for use below 0°C)
- Enclosure allows for side conduit entry

TECHNICAL DETAILS

- 3 hours operation on battery power after mains power failure
- Can be installed as maintained or non-maintained. Details in instructions.
- 30m maximum viewing distance

ATTACHMENTS

LEGENDS Alternative legends available as listed

ORDER CODE	DESCRIPTION
NLE/3/LED/M3	Lexington Exit Box 3W LED Maint 3Hr Euro Down Legend
NLE/3/LED/M3/ISO-U	Lexington Exit Box 3W LED Maint 3Hr ISO Up Legend
ATTACHMENTS	
NLE/LE/UP	Lexington Euro Legend Up
NLE/LE/DOWN	Lexington Euro Legend Down
NLE/LE/LEFT	Lexington Euro Legend Left
NLE/LE/RIGHT	Lexington Euro Legend Right
NLE/V2/LE/UP	Lexington V2 ISO Legend Up
NLE/V2/LE/DOWN	Lexington V2 ISO Legend Down
NLE/V2/LE/LEFT	Lexington V2 ISO Legend Left
NLE/V2/LE/RIGHT	Lexington V2 ISO Legend Right

