



Main

Device short name	FDM121
Product or component type	Display module
Accessory / separate part category	Display and signalling accessory
Range compatibility	Compact NSX Masterpact NT Masterpact NW Compact NS630b...1600 Compact NS1600b...3200 PowerPact H PowerPact J PowerPact L PowerPact Multistandard PowerPact P PowerPact R
Offer type	C4 C5
Product name	Enerlin'X FDM
Function of module	Remote control View network Metering Display alarm

Complementary

Control type	Remote control
Mounting mode	Flush mounting
Mounting support	Surface mount with kit
Display type	LCD screen with white backlighting
Display resolution	128 x 128 pixels
View angle horizontal x vertical	60 x 30°
[Us] rated supply voltage	24 V DC - 20...10 %
Current consumption	21 mA
Standards	CE CSA UL
Height	96 mm
Width	96 mm
Depth	30 mm
Accessory / separate part category	Spare part for Compact NS630b...1600 Spare part for Compact NS1600b...3200

Environment

IP degree of protection	IP54
Ambient air temperature for operation	-10...55 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------