



QQGQ8.E196145

Power Supplies, Information Technology Equipment Including Electrical Business Equipment Certified for Canada - Component

[Page Bottom](#)

Power Supplies, Information Technology Equipment Including Electrical Business Equipment Certified for Canada - Component

[See General Information for Power Supplies, Information Technology Equipment Including Electrical Business Equipment Certified for Canada - Component](#)

ABB STOTZ-KONTAKT GMBH
HAUPTSTRASSE 14-16
78132 HORNBERG, GERMANY


E196145

Model No.	Rated Input			Max Output			OC	SP	EP	FC	GC
	Volts	Hz	SC	V	A	VA					
CP-A CM[*r]	13 - 30dc	-	3	30dc	0.1	3	3	60950-1	20B	0	0
CP-A RU	10-40dc	-	3	39.4dc	40	157.6	3	60950-1	20B	0	0
CP-ASI /2.8											
	100-120/ 200-240 115/ 230ac	50/60	0	30.7dc	3.1	88.5	1/3	60950	15B	5	1
CP-ASI /4.0[*r]											
	100-120/ 220-240Vac,240-300Vdc	50-60	0	30.5dc	4	-	3	60950-1	20	5	1
CP-ASI /4.0 DC/DC											
	24dc	-	3	30.4dc	7.3	150.2	3	60950-1	-	5	1
CP-ASI /8.0											
	100-120/ 220-240ac	50-60	0	30.3	10.05	304.4	3	60950	15B	5	1
CP-C 24/10.0[*r]											
	110-240ac	48-63	0	24dc	10	240	3	60950-1	-	0	1
CP-C 24/20.0[*r]											
	110-240ac	48-63	0	24dc	20	480	-	60950-1	20B	0	1
CP-C 24/5.0											
	110-240ac	48-63	0	28	12	225	3	60950-1	-	0	1
CP-D 12/0.83											
	100-240ac	47-63	0	12.07	1.31	13.44	3	60950-1	20B	0	2
CP-D 12/2.1[*r]											
	100-240ac	47-63	0	12	2.1	-	-	60950-1	20B	0	2
CP-D 12/4.5											
	100-240ac	47-63	0	12.05dc	6	53.4	3	60950-1	20B	0	2
CP-D 12/6.0											
	100-240ac	47-63	0	12.02	9.11	90.1	3	60950-1	20B	0	2
CP-D 15/0.67											
	100-240ac	47-63	0	14.94	1.25	14.24	3	60950-1	20B	0	2
CP-D 15/2.0											
	100-240ac	47-63	0	15.1dc	3.67	38.05	3	60950-1	20B	0	2
CP-D 15/4.0											

	100-240ac	47-63	0	15.01dc	5.6	64.87	3	60950-1	20B	0	2
CP-D 15/5.0											
	100-240ac	47-63	0	15.023	8.76	98.2	3	60950-1	20B	0	2
CP-D 24/0.42											
	100-240ac	47-63	0	23.94	0.8	15.8	3	60950-1	20B	0	2
CP-D 24/1.3											
	100-240ac	47-63	0	24.08dc	3.1	37.52	3	60950-1	20B	0	2
CP-D 24/2.5											
	100-240ac	47-63	0	24.02dc	3.88	72.22	3	60950-1	20B	0	2
CP-D 24/3.8											
	100-240ac	47-63	0	24	3.8	91	3	60950-1	20B	0	2
CP-D 24/4.2											
	100-240ac	47-63	0	24.08	7.71	122.58	3	60950-1	20B	0	2
CP-D 5/1.5											
	100-240ac	47-63	0	4.99	2.54	10.36	3	60950-1	20B	0	2
CP-D 5/12.0											
	100-240ac	47-63	0	5.035	17.2	52.64	3	60950-1	20B	0	2
CP-D 5/3.0											
	100-240ac	47-63	0	5.038dc	7	21.8	3	60950-1	20B	0	2
CP-D 5/7.0											
	100-240ac	47-63	0	5.02dc	9.9	35.43	3	60950-1	20B	0	2
CP-E 12/1.5[*r]											
	100-240ac	47-63	0	12dc	-	18	3	60950-1, 2nd	20B	1	0
CP-E 12/10.0											
	115/ 220/ 230ac	47-63	0	12.02	14	124.68	3	60950-1	20B	0	1
CP-E 12/2.5											
	100-240ac	47-63	0	14.96dc	4	45.88	3	60950-1	20B	0	1
CP-E 12/5.0											
	100-240ac	47-63	0	14.76dc	7	87	3	60950-1	20B	0	1
CP-E 15/1.2[*r]											
	100-240ac	47-63	0	15dc	-	18	3	60950-1, 2nd	20B	1	0
CP-E 24/0.75[*r]											
	100-240ac	47-63	0	24dc	-	18	3	60950-1, 2nd	20B	1	0
CP-E 24/1.25											
	120-240ac	47-63	0	24dc	-	30	3	60950-1	20B	0	1
CP-E 24/10.0											
	115/ 230ac	47-63	0	24dc	14.5	308.1	3	60950-1	20B	0	1
CP-E 24/2.5											
	100-240ac	47-63	0	28.5dc	3.48	91.45	3	60950-1	20B	0	1
CP-E 24/20.0											
	115/ 230ac	47-63	0	24.07dc	27.3	567.1	3	60950-1	20B	0	0
CP-E 24/5.0											
	115/ 220/ 230ac	47-63	0	24.07	7.6	131.7	3	60950-1	20B	0	1

CP-E 48/0.62											
	100-240ac	47-63	0	56.87dc	0.93	42	3	60950-1	20B	0	1
CP-E 48/1.25											
	100-240ac	47-63	0	28.5dc	3.48	91.45	3	60950-1	20B	0	1
CP-E 48/10.0											
	115/ 230ac	47-63	0	48.05dc	13.5	583.9	3	60950-1	20B	0	0
CP-E 48/5.0[*r]											
	115/ 230ac	47-63	0	48dc	5	240	3	60950-1	20B	0	1
CP-E 5/3.0[*r]											
	100-240ac	47-63	0	5dc	-	15	3	60950-1, 2nd	20B	1	0
CP-E 5/6.0											
	100-240ac	47-63	0	5.87dc	7.9	41.38	3	60950-1	20B	0	1
CP-S 24/10.0[*r]											
	110-120/ 220-240ac	48-63	0	24dc	10	240	3	60950-1	-	0	1
CP-S 24/20.0[*r]											
	110-240ac	48-63	0	24dc	20	480	-	60950-1	20B	0	1
CP-S 24/5.0											
	110-240ac	48-63	0	24	12.5	176	3	60950-1	-	0	1
CP-T 24/10.0											
	3PH 400-500Vac	47-63	0	24.1dc	13.7	289.92	3	60950-1	20B	0	1
CP-T 24/20.0											
	3PH 400-500ac	47-63	0	24.1	29.6	513	3	60950-1	20B	0	1
CP-T 24/40.0											
	3PH 400-500Vac	47-63	0	24.1dc	44.5	1038	3	60950-1	20B	0	1
CP-T 24/5.0											
	3PH 400-500Vac	47-63	0	24.08dc	6.95	152.32	-	60950-1	20B	0	1
CP-T 48/10.0											
	3PH 400-500ac	47-63	0	48.2	19.7	498	3	60950-1	20B	0	1
CP-T 48/20.0											
	3PH 400-500Vac	47-63	0	48.1dc	27.5	1176	3	60950-1	20B	0	1
CP-T 48/5.0											
	3PH 400-500Vac	47-63	0	48.03dc	6.32	279.93	3	60950-1	20B	0	1
Syston PS TSL 24V/20A											
	100-120/ 208-240/ 115/ 230ac	50/60	0	54	21.5	516	3	1950	-	0	1

[*r] - Output values are rated.

Marking: Company name or trademark   , catalog designation and Recognized Component Mark for Canada,

 on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2012-11-21

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".