

Main

Range	MGF fusegear
Product or component type	Enclosed switch disconnecter fuse
Poles description	3P + N
[Ue] rated operational voltage	415 V
[Ie] rated operational current	32 A

Complementary

Mechanical interlocking	Door interlocking function
Network type	AC
Network frequency	50/60 Hz
Utilisation category	AC-23B AC-22A AC-20A AC-21A
[Uimp] rated impulse withstand voltage	6 kV
[Icw] rated short-time withstand current	416 kA
[Icm] rated short-circuit making capacity	1.35 kA
Maximum power	15 kW
Cable cross section	10 mm²
Fuse type	BS88
Fuse size	A2 A1
Associated fuse rating	32 A
Control type	Handle
Provision for padlocking	Handle padlockable in on and off position
Contact position indicator	Yes
Provided equipment	Earthing kit Fuse links Removable gland plate with cable knockouts

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------