

Main

Range of product	MGF fusegear
Product or component type	Enclosed switch disconnecter
Poles description	3P + N
[Ue] rated operational voltage	415 V
[Ie] rated operational current	100 A

Complementary

Mechanical interlocking	Door interlocking function
Network type	AC
Network frequency	50/60 Hz
Utilisation category	AC-20A AC-23B AC-21A AC-22A
[Uimp] rated impulse withstand voltage	6 kV
[Icw] rated short-time withstand current	1300 kA
[Icm] rated short-circuit making capacity	3.5 kA
Maximum power	55 kW
Control type	Handle
Provision for padlocking	Handle padlockable in on and off position
Cable cross section	50 mm ²
IP degree of protection	IP41
Standards	BS EN 60947-3
Contact position indicator	Yes
Provided equipment	Removable gland plate with cable knockouts Earthing kit

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------