

**WQV 6/10****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

**General ordering data**

|            |                                                                      |
|------------|----------------------------------------------------------------------|
| Version    | W-Series, Cross-connector, For the terminals,<br>Number of poles: 10 |
| Order No.  | <a href="#">1052260000</a>                                           |
| Type       | WQV 6/10                                                             |
| GTIN (EAN) | 4008190153977                                                        |
| Qty.       | 20 pc(s).                                                            |

## WQV 6/10

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 18 mm   | Depth (inches)  | 0.709 inch |
| Height     | 77.3 mm | Height (inches) | 3.043 inch |
| Width      | 7.6 mm  | Width (inches)  | 0.299 inch |
| Net weight | 16.75 g |                 |            |

## Temperatures

|                                  |                |                                  |        |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature              | -25 °C...55 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C         |                                  |        |

## Material data

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | PA 66 | Colour | yellow |
| UL 94 flammability rating | V-0   |        |        |

## System specifications

|         |                   |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

## Additional technical data

|                     |                 |                |                 |
|---------------------|-----------------|----------------|-----------------|
| Installation advice | Direct mounting | Type of fixing | when screwed in |
|---------------------|-----------------|----------------|-----------------|

## Cross-connector

|                                          |              |                           |                 |
|------------------------------------------|--------------|---------------------------|-----------------|
| Number of cross-connected terminals      | 10           | Rated current, multi-pole | 57 A            |
| Tightening torque range for fixing screw | 0.5...1.0 Nm | Type                      | Cross-connector |

## Dimensions

|                 |      |              |       |
|-----------------|------|--------------|-------|
| Pitch in mm (P) | 8 mm | TS 35 offset | 28 mm |
|-----------------|------|--------------|-------|

## General

|                     |                 |                 |    |
|---------------------|-----------------|-----------------|----|
| Installation advice | Direct mounting | Number of poles | 10 |
|---------------------|-----------------|-----------------|----|

## Rating data

|               |      |
|---------------|------|
| Rated current | 57 A |
|---------------|------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 | ECLASS 12.0 | 27-14-11-40 |

## Approvals

Approvals



ROHS

Conform

Creation date 22 October 2022 10:58:51 CEST

Catalogue status 07.10.2022 / We reserve the right to make technical changes.

## WQV 6/10

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

|                                             |                                                                                          |
|---------------------------------------------|------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">EAC certificate</a>                                                          |
| Engineering Data                            | <a href="#">CAD data – 08861_WQV_6-10_DXF.dxf</a><br><a href="#">CAD data – STEP</a>     |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                 |
| User Documentation                          | <a href="#">Beipackzettel_WQV.pdf</a><br><a href="#">StorageConditionsTerminalBlocks</a> |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>                                                 |
| Brochures                                   |                                                                                          |