

**QL 2 ST5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

**General ordering data**

|            |                            |
|------------|----------------------------|
|            |                            |
| Order No.  | <a href="#">3834300000</a> |
| Type       | QL 2 ST5                   |
| GTIN (EAN) | 4008190456955              |
| Qty.       | 20 pc(s).                  |

**QL 2 ST5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 1 mm    | Depth (inches)  | 0.039 inch |
| Height     | 16.3 mm | Height (inches) | 0.642 inch |
| Width      | 17.5 mm | Width (inches)  | 0.689 inch |
| Net weight | 2.311 g |                 |            |

**Temperatures**

|                     |                |
|---------------------|----------------|
| Storage temperature | -25 °C...55 °C |
|---------------------|----------------|

**Material data**

|          |       |        |      |
|----------|-------|--------|------|
| Material | Cu Zn | Colour | grey |
|----------|-------|--------|------|

**System specifications**

|         |                           |
|---------|---------------------------|
| Version | for cross-connection link |
|---------|---------------------------|

**Additional technical data**

|                |                 |
|----------------|-----------------|
| Type of fixing | when screwed in |
|----------------|-----------------|

**Dimensions**

|                 |         |
|-----------------|---------|
| Pitch in mm (P) | 16.3 mm |
|-----------------|---------|

**General**

|                 |   |
|-----------------|---|
| Number of poles | 2 |
|-----------------|---|

**Rating data**

|               |      |                          |      |
|---------------|------|--------------------------|------|
| Rated current | 41 A | Current at maximum wires | 41 A |
|---------------|------|--------------------------|------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 | ECLASS 12.0 | 27-14-11-40 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Engineering Data   | <a href="#">CAD data – STEP</a>                 |
| Engineering Data   | <a href="#">EPLAN, WSCAD</a>                    |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>        |