

G 20/0.25A/F**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

For protection against overcurrent, we offer cartridge fuse with dimensions 5x20 mm in sizes from 100 mA to 6.3 A.

General ordering data

Version	Active components, Fuse
Order No.	0430500000
Type	G 20/0.25A/F
GTIN (EAN)	4008190153991
Qty.	10 pc(s).

G 20/0.25A/F**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	5 mm	Depth (inches)	0.197 inch
Height	20 mm	Height (inches)	0.787 inch
Width	5 mm	Width (inches)	0.197 inch
Net weight	0.9 g		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1	SCIP	e55693ba-5f1b-4f6e-b99e-8d57d3de2235
------------	----------------	------	--------------------------------------

Material data

Colour	Light Grey
--------	------------

System specifications

Version	Fuse accessories
---------	------------------

Fuse cartridges

Cartridge fuse	G-Si. 5 x 20	Characteristics	quick-acting
Colour	Light Grey	Current	0.25 A
Melting integral	0.07 A ² s	Optical function display	No
Power output (@ 1.5 In)	0.3 W	Rated breaking capacity	1.5 kA
Version	Fuse accessories	Voltage drop	280 mV

Rating data

Rated voltage	250 V AC	Rated current	0.25 A
---------------	----------	---------------	--------

Classifications

ETIM 6.0	EC000035	ETIM 7.0	EC000035
ETIM 8.0	EC002704	ECLASS 9.0	27-14-20-01
ECLASS 9.1	27-14-20-01	ECLASS 10.0	27-14-20-01
ECLASS 11.0	27-14-20-01	ECLASS 12.0	27-14-20-01

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	CAD data – STEP
Engineering Data	EPLAN, WSCAD
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	