

APG 80**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Crimping tools for cable lugs, connectors and wire-end ferrules with interchangeable inserts**

- extremely fast processing thanks to hydraulic support
- large processing range up to 400 mm²
- 360° revolving quick action crimping head
- automatic pressure limitation and monitoring via pressure sensor
- Additional features for APG series:
- electronic control and monitoring of the crimping process
- Saving of all crimping cycles and error messages to internal memory
- Reading of all cycles and error messages via USB

General ordering data

Version	6mm ² , 400mm ²
Order No.	1502390000
Type	APG 80
GTIN (EAN)	4050118310627
Qty.	1 pc(s).
Delivery status	This article will no longer be available in the future.
Available until	2022-02-04

APG 80

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	95 mm	Depth (inches)	3.74 inch
Height	310 mm	Height (inches)	12.205 inch
Width	406 mm	Width (inches)	15.984 inch
Net weight	8,360 g		

Technical data

Charging time	1 h		
Operating voltage	14.4 V		
Pressing force	nominal	80 kN	

Description of contact

Crimping range, max.	400 mm ²	Crimping range, min.	6 mm ²
----------------------	---------------------	----------------------	-------------------

tool data crimping

Drive	Battery-operated hydraulic system
-------	-----------------------------------

Classifications

ETIM 6.0	EC000168	ETIM 7.0	EC000168
ETIM 8.0	EC000168	ECLASS 9.0	21-04-38-11
ECLASS 9.1	36-63-06-90	ECLASS 10.0	21-04-38-11
ECLASS 11.0	21-04-38-11	ECLASS 12.0	21-04-38-11

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	1502390000_DECLARATION_OF_CONFORMITY.pdf
User Documentation	Manual
Catalogues	Catalogues in PDF-format
Brochures	

APG 80

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

