



SAFETY DATA SHEET AUTO CLEEN DE-ICER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name AUTO CLEEN DE-ICER

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier Cleenol Group Ltd
Neville House
Beaumont Road
Banbury
Oxon OX16 1RB
UK
Tel : +44 (0)1295 251721
Fax : +44 (0)1295 269561
sales@cleenol.co.uk

1.4. Emergency telephone number

Emergency telephone Emergency contact number (9am to 5pm Monday to Friday excluding bank holidays): 01295 251721 ask for technical, quoting the product name.
Emergency Action: In the event of a medical enquiry involving this product outside of these hours, please contact your doctor or local hospital accident and emergency department or the NHS enquiry service (dial 111) again quoting product name and where applicable present this MSDS to the medical professional.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226
Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi;R36. R67,R10.

2.2. Label elements

Pictogram



Signal word Warning

AUTO CLEEN DE-ICER

Hazard statements	H226 Flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P280 Wear protective gloves. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/ doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/ attention. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.

Contains PROPAN-2-OL

Supplementary precautionary statements P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PROPAN-2-OL		30-60%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-0000
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Xi;R36 R67	
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention immediately.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

AUTO CLEEN DE-ICER

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Use explosion proof electric equipment.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

SHELF LIFE OF DILUTION

12 MONTHS

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

AUTO CLEEN DE-ICER

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

pH 10-12

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat. Avoid contact with the following materials: Oxidising agents. Reducing agents.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute and chronic health hazards

Inhalation May cause respiratory system irritation. SKIN CONTACT. Irritating to skin. Product has a defatting effect on skin. May cause allergic contact eczema. EYE CONTACT. Irritating to eyes. INGESTION. May cause stomach pain or vomiting.

AUTO CLEEN DE-ICER

SECTION 12: Ecological Information

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1993

UN No. (IMDG) 1993

UN No. (ICAO) 1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID) FLAMMABLE LIQUID, N.O.S.

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S.

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S.

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID label 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

AUTO CLEEN DE-ICER

14.6. Special precautions for user

EmS	F-E, S-E
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972. The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	System of specific information relating to Dangerous Preparations. 2001/58/EC.
Guidance	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date	29/09/2017
Revision	6
Supersedes date	05/05/2017
SDS number	M4A
Risk phrases in full	R10 Flammable. R11 Highly flammable. R36 Irritating to eyes. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.