NVC UK - NVC Lighting Limited NVC Park 201, Hollymoor Way, Rubery, Birmingham, B31 5HE T +44 (0)121 457 6340 E sales@nvcuk.com NVC NORDICS - NVC Lighting AB Albybergsringen 3b 137 69 Österhaninge T +46(0)8 735 55 40 Sweden info@nvc-lighting.se Finland info@nvclighting.fi Denmark info@nvclighting.dk



DATASHEET

FULTON

Fulton Surface Mount Kit White For 600X600 Panel

Surface Mounting Installations Aluminium Construction with White PC Corners Quick and Easy To Assemble

GENERAL INFORMATION	
Product Code	NFU/SMK/66
Product Range	LED Panels
Product Category	LED Panels
IP Rating	N/A
IK Rating	N/A
Warranty	N/A
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=43
Dimensions Square/Rectangular (L x W x H) (mm)	L=600, W=600, H=N/A
Cut-out Size (mm)	N/A
Product Weight (Kg)	0.7
CONSTRUCTION	
Body Material	PC
Body Colour	White
Optical Material	N/A
Optical Finnish	N/A
Termination	N/A
Driver - Intergal or Remote	N/A
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight inlc. Carton (Kg)	N/A



LUMINAIRE PERFORMANCE		
Energy Rating	N/A	
Luminaire Lumens (Im)	N/A	
Power Consumption (W)	N/A	
LED Lumens (Im/W)	N/A	
Efficacy (I.Im/c.W)	N/A	
Operating Temp. (Min/Max)	N/A N/A	
LIGHT SOURCE		
Туре	N/A	
Correlated Colour Temp.	N/A	
Correlated Rendering Index (CRI)	N/A	
Lumen Depreciation	N/A	
SDCM	N/A	
ELECTRICAL INPUT		
VOLTAGE (V)	N/A	
Operating Frequency	N/A	
In Rush	N/A	
Drivers per MCB*	N/A	
Class	N/A	
Power Factor	N/A	
Cable Entry	N/A	
ELECTRICAL OUTPUT		
Forward Current (mA)	N/A	
Forward Voltage (Vf)	N/A	
EMERGENCY DATA		
Mode of Operation	N/A	
Battery Duration	N/A	
Battery Type	N/A	
Battery Specification	N/A	
Ballast Lumen Factor (BLF)	N/A	
DIMMING		
DALI	N/A	
OTHER	N/A	
Switch Dim	N/A	
Corridor Function	N/A	
SENSORS		
Microwave	N/A	
PIR	N/A	
STANDARDS/APPROVALS		
CE Marked	Yes	
Certificate of Conformity	Yes	
Accreditations	N/A	
BARCODE		
EAN NUMBER	5055943016088	
E NUMBER	7014144	
S NUMBER	4256504	

^{*} GUIDE ONLY













