

NVC UK - NVC Lighting Limited
NVC Park 201, Hollymoor Way, Rubery,
Birmingham, B31 5HE
T +44 (0)121 457 6340
E sales@nvcuk.com

NVC NORDICS - NVC Lighting AB
Albybergsringen 3b 137 69 Österhaninge
T +46(0)8 735 55 40
Sweden info@nvc-lighting.se
Finland info@nvc-lighting.fi
Denmark info@nvc-lighting.dk



DATASHEET

CLEVELAND

Cleveland LED Single 5Ft IP65 Non Corrosive M3 840

IP65 Non-Corrosive LED Fitting
Strong PC Enclosure & Stainless Steel Clips
ENEC Approved Flicker Free Driver



GENERAL INFORMATION	
Product Code	NCV1X5/M3/840
Product Range	Industrial
Product Category	Industrial
IP Rating	65
IK Rating	IK10
Warranty	5 Years Unlimited
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=1550, W=65, H=70
Cut-out Size (mm)	N/A
Product Weight (Kg)	2.13
CONSTRUCTION	
Body Material	PC
Body Colour	Grey
Optical Material	N/A
Optical Finish	N/A
Termination	4x2x2.5mm sq. Push In Terminal
Driver - Integal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight inc. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	3935
Power Consumption (W)	35
LED Lumens (lm/W)	150
Efficacy (l.lm/c.W)	110
Operating Temp. (Min/Max)	0°C to 20°C to
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Correlated Rendering Index (CRI)	>80
Lumen Depreciation	L70 50000
SDCM	<5
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50
In Rush	<25A
Drivers per MCB*	B10=20 B16=30 C10=30 C16=40
Class	Class 1
Power Factor	>0.95
Cable Entry	Side / Base
ELECTRICAL OUTPUT	
Forward Current (mA)	570
Forward Voltage (Vf)	57
EMERGENCY DATA	
Mode of Operation	Maintained
Battery Duration	3 Hours
Battery Type	NiCd
Battery Specification	6V 1.8Ah
Ballast Lumen Factor (BLF)	0.06
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5055943066502

* GUIDE ONLY

