

NVC UK - NVC Lighting Limited  
NVC Park 201, Hollymoor Way, Rubery,  
Birmingham, B31 5HE  
T +44 (0)121 457 6340  
E sales@nvcuk.com

NVC NORDICS - NVC Lighting AB  
Albybergsringen 3b 137 69 Österhaninge  
T +46(0)8 735 55 40  
Sweden info@nvc-lighting.se  
Finland info@nvc-lighting.fi  
Denmark info@nvc-lighting.dk



DATASHEET

CLEVELAND

Cleveland LED Twin 6Ft IP65 Non Corrosive 840

IP65 Non-Corrosive LED Fitting  
Strong PC Enclosure & Stainless Steel Clips  
ENEC Approved Flicker Free Driver



| GENERAL INFORMATION                            |                                |
|------------------------------------------------|--------------------------------|
| Product Code                                   | NCV2X6/840                     |
| Product Range                                  | Industrial                     |
| Product Category                               | Industrial                     |
| IP Rating                                      | 65                             |
| IK Rating                                      | IK10                           |
| Warranty                                       | 5 Years Unlimited              |
| DIMENSION/WEIGHT                               |                                |
| Dimensions Circular (DIA x H) (mm)             | DIA=N/A, H=N/A                 |
| Dimensions Square/Rectangular (L x W x H) (mm) | L=1850, W=110, H=70            |
| Cut-out Size (mm)                              | N/A                            |
| Product Weight (Kg)                            | 2.8                            |
| CONSTRUCTION                                   |                                |
| Body Material                                  | PC                             |
| Body Colour                                    | Grey                           |
| Optical Material                               | N/A                            |
| Optical Finish                                 | N/A                            |
| Termination                                    | 3x2x2.5mm sq. Push In Terminal |
| Driver - Integal or Remote                     | Integral                       |
| PACKAGING                                      |                                |
| Carton Dimensions (mm)                         | N/A                            |
| Quantity per Outer Carton                      | N/A                            |
| Total Weight inc. Carton (Kg)                  | N/A                            |

| LUMINAIRE PERFORMANCE            |                             |
|----------------------------------|-----------------------------|
| Energy Rating                    | N/A                         |
| Luminaire Lumens (lm)            | 9194                        |
| Power Consumption (W)            | 74                          |
| LED Lumens (lm/W)                | 150                         |
| Efficacy (l.lm/c.W)              | 115                         |
| Operating Temp. (Min/Max)        | -20°C to 25°C               |
| LIGHT SOURCE                     |                             |
| Type                             | LED                         |
| Correlated Colour Temp.          | 4000                        |
| Correlated Rendering Index (CRI) | >80                         |
| Lumen Depreciation               | L70 50000                   |
| SDCM                             | <5                          |
| ELECTRICAL INPUT                 |                             |
| VOLTAGE (V)                      | 220-240V AC                 |
| Operating Frequency              | 50                          |
| In Rush                          | <25A                        |
| Drivers per MCB*                 | B10=10 B16=15 C10=15 C16=20 |
| Class                            | Class 1                     |
| Power Factor                     | >0.95                       |
| Cable Entry                      | Side / Base                 |
| ELECTRICAL OUTPUT                |                             |
| Forward Current (mA)             | 2 x 500                     |
| Forward Voltage (Vf)             | 70                          |
| EMERGENCY DATA                   |                             |
| Mode of Operation                | N/A                         |
| Battery Duration                 | N/A                         |
| Battery Type                     | N/A                         |
| Battery Specification            | N/A                         |
| Ballast Lumen Factor (BLF)       | N/A                         |
| DIMMING                          |                             |
| DALI                             | N/A                         |
| OTHER                            | N/A                         |
| Switch Dim                       | N/A                         |
| Corridor Function                | N/A                         |
| SENSORS                          |                             |
| Microwave                        | N/A                         |
| PIR                              | N/A                         |
| STANDARDS/APPROVALS              |                             |
| CE Marked                        | Yes                         |
| Certificate of Conformity        | Yes                         |
| Accreditations                   | N/A                         |
| BARCODE                          |                             |
| EAN NUMBER                       | 5055943071865               |

\* GUIDE ONLY

