

NVC UK - NVC Lighting Limited
 NVC Park 201, Hollymoor Way, Rubery,
 Birmingham, B31 5HE
 T +44 (0)121 457 6340
 E sales@nvcuk.com

NVC NORDICS - NVC Lighting AB
 Albybergströgen 3b 137 69 Österhaninge
 T +46(0)8 735 55 40
 Sweden info@nvc-lighting.se
 Finland info@nvc-lighting.fi
 Denmark info@nvc-lighting.dk



DATASHEET

TEXAS PRO

Texas Pro LED Single 6Ft Batten 840

IP20 Surface LED Fitting
 Steel And Polycarbonate Construction
 ENEC Approved Flicker Free Driver



GENERAL INFORMATION	
Product Code	NTE1X6/PRO/840
Product Range	Surface Mount
Product Category	Surface Mount
IP Rating	20
IK Rating	N/A
Warranty	7 Years
DIMENSION/WEIGHT	
Dimensions Circular (DIA x H) (mm)	DIA=N/A, H=N/A
Dimensions Square/Rectangular (L x W x H) (mm)	L=1800, W=63, H=74
Cut-out Size (mm)	N/A
Product Weight (Kg)	1.46
CONSTRUCTION	
Body Material	PC/Steel
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	3x2x2.5mm sq. Push In Terminal
Driver - Interal or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	6139
Power Consumption (W)	44
LED Lumens (lm/W)	180
Efficacy (l.lm/c.W)	140
Operating Temp. (Min/Max)	-20°C to 25°C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Correlated Rendering Index (CRI)	>80
Lumen Depreciation	L80 100000
SDCM	<3
ELECTRICAL INPUT	
VOLTAGE (V)	220-240V AC
Operating Frequency	50
In Rush	<25A
Drivers per MCB*	B10=10 B16=15 C10=15 C16=20
Class	Class 1
Power Factor	>0.95
Cable Entry	Side / Base
ELECTRICAL OUTPUT	
Forward Current (mA)	N/A
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	Yes
Certificate of Conformity	Yes
Accreditations	N/A
BARCODE	
EAN NUMBER	5055943094468

* GUIDE ONLY

