

Product Code: MD002SS

Description: 10AX Ingot 2 Way Switch Module



## General Information

|                                 |                                                                                                                                              |                                                                                     |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Dimensions (mm)                 | 25 (W) x 53 (H) x 20 (D)                                                                                                                     |                                                                                     |
| Finish                          | Stainless Steel                                                                                                                              |                                                                                     |
| Materials                       | Rocker Switch: Urea<br>Switch Cover: Stainless Steel<br>Terminal Screws: Steel & Yellow Passivated<br>Internal Busbars: Formed Pressed Brass | Rear Housing: Nylon<br>Terminals: Brass<br>Contacts: Silver "on-lay" Copper / Brass |
| Rated Voltage (V~) (Ue)         | 250                                                                                                                                          | Frequency (Hz) 50                                                                   |
| Inductive Load Rating (AX)      | 10                                                                                                                                           |                                                                                     |
| Load Rating Comments            | Suitable for Inductive Loads                                                                                                                 |                                                                                     |
| Termination Type                | Screw                                                                                                                                        |                                                                                     |
| Terminal Size (mm)              | Ø3.5                                                                                                                                         | Terminal Torque Value (Nm) 0.5                                                      |
| Terminal Capacity - Solid (mm²) | 4 x 1.5 or 2 x 2.5                                                                                                                           |                                                                                     |
| Modular Rocker Switches         | Yes                                                                                                                                          |                                                                                     |
| 2 Way Switch                    | Yes                                                                                                                                          |                                                                                     |
| Minimum Back Box Depth (mm)     | 16 (25 Flat Plate)                                                                                                                           |                                                                                     |
| Operational Temperature (°C)    | -5 to +40                                                                                                                                    |                                                                                     |
| Warranty (Years)                | 10                                                                                                                                           |                                                                                     |

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.