

Product Code: MD017BK

Description: 20A Flex Outlet Module



General Information

Dimensions (mm)	25 (W) x 56.5 (H) x 30 (D)	
Finish	Black	
Insert Colour	Black	
Materials	Blank: Urea Terminals: Brass Bracket: Mild Steel Screws: Nickel Plated Steel	Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Cord Grip: Nylon
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
Flex Outlet Available	Yes	
Flex Outlet Location	Front of Plate	Flex Outlet Dimension (mm) Ø10
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.