

Product Code: MD018WH-FF

Description: 13A/10AX Double Pole Switch Module



General Information

Dimensions (mm)	25 (W) x 53 (H) x 20 (D)	
Finish	Click White	
Materials	Rocker Switch: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass	Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass
Anti Microbial Certified	Yes	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable For Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm ²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
Double Pole Switch	Yes	
Product Marking	Fridge Freezer	
Minimum Back Box Depth (mm)	16 (25 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches both the Deco white range and Metal Clad range.