



## CLICK® ScolmoreGROUP

## **Technical Specification**

Product Code: PRW019 Description: 10AX 4 Gang 2 Way Plate Switch





## **General Information**

Plate Dimensions (mm)  $146 \text{ (W)} \times 86 \text{ (H)} \times 11 \text{ (D)}$ 

Plate Fixing Centres - Horizontal (mm) 120.6

MiniGrid Plate (Gang) 2

MiniGrid Single Width Module Quantity 2 x 2

MiniGrid Double Width Module Quantity 2

Style Square Edge
Finish Polar White

Materials Front Plate: U

erials Front Plate: Urea
Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass Anti Microbial Certified Yes

Rated Voltage (V~) (Ue) 250 Inductive Load Rating (AX) 10

Load Rating Comments Suitable for Inductive Loads

Termination Type Screw
Terminal Size (mm) Ø3.5

Terminal Capacity - Solid (mm²) 4 x 1.5 or 2 x 2.5

Modular Rocker Switches Yes

2 Way Switch Yes

Minimum Back Box Depth (mm) 16

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 20

Standards BS EN 60669-1

Frequency (Hz) 50

Rear Housing: Nylon

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Terminal Torque Value (Nm) 0.5

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Interchangeable with modules in the MiniGrid Range





