

Technical Specification



Product Code: MD023PW Description: 20A Double Pole Switch With Neon Module





Rear Housing: Nylon

Contacts: Silver "on-lay" Copper / Brass

General Information

 $\textbf{Dimensions (mm)} \quad 41 \text{ (W)} \times 52.5 \text{ (H)} \times 22 \text{ (D)}$

Finish Polar White

Materials Rocker Switch: Urea

Neon Cover: Polycarbonate Terminals: Brass

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Anti Microbial Certified Yes

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 20

Termination Type Screw

Terminal Size (mm) Ø4.4 Terminal Torque Value (Nm) 1.2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Modular Rocker Switches Yes

Double Pole Switch Yes

Neon Indicator Yes Indicator Colour Orange

Minimum Back Box Depth (mm) 25 (35 Flat Plate)
Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS EN 60669-1

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges

