

Product Code: VPCH051WH

Description: 13A Double Pole Switched Fused Connection Unit With Optional Flex Outlet



General Information

Plate Dimensions (mm)	88 (W) x 88 (H) x 8 (D)
Dimensions With Gasket (mm)	91 (W) x 91 (H) x 9 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
Style	Victorian
Finish	Polished Chrome
Insert Colour	White
Gasket Colour	White
Materials	Front Plate: Stainless Steel Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel
Anti Microbial Certified	No
Rated Voltage (V~) (Ue)	250
Resistive Load Rating (A)	13
Fuse Fitted Rating & Type	13A (BS 1362)
Termination Type	Screw
Terminal Size (mm)	Ø5
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4
Switched	Yes
Double Pole Switch	Yes
Twin Earth Terminals	Yes
Product Marking	Fused
Flex Outlet Available	Yes
Flex Outlet Location	Front of Plate
Minimum Back Box Depth (mm)	25
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	10
Standards	BS 1363-4 BS 1362

Insert, Switch, Fuse Drawer & Housing: Urea
Terminal Screws: Steel & Yellow Passivated
Internal Busbars: Formed Pressed Brass
Gasket: Nylon

Frequency (Hz) 50

Terminal Torque Value (Nm) 2

Flex Outlet Dimension (mm) Ø10

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.