

Product Code: PRW100

Description: 115V/230V Dual Voltage Shaver Socket Outlet



General Information

Plate Dimensions (mm)	86 (W) x 146 (H) x 11 (D)
Plate Fixing Centres - Horizontal (mm)	120.6
Style	Square Edge
Finish	Polar White
Materials	Front Plate: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel
Anti Microbial Certified	Yes
Rated Voltage (V~) (Ue)	240
Load Rating @115V (Va)	20
Load Rating @230V (Va)	20
Thermal Protection Device	PTC Resettable Fuse
Termination Type	Screw
Terminal Size (mm)	Ø3.5
Terminal Capacity - Solid (mm ²)	2 x 1.5 or 1 x 2.5
Socket Features	Safety Interlock Shutter
Twin Earth Terminals	Yes
Product Marking	Shavers Only, 230V~, 115V~
Minimum Back Box Depth (mm)	47
Ingress Protection	IP21
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20
Standards	BS EN IEC 61558-1 BS EN 61558-2-5

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20VA at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms.

PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.