

Product Code: CL035

Description: 13A 1 Gang Double Pole Switched Socket Outlet



General Information

Dimensions (mm)	80 (W) x 80 (H) x 42 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Metal Clad		
Finish	Metal Clad Grey		
Materials	Front Plate & Mounting Box:		Insert & Rocker Switch: Urea
	Electrophoretically Coated Steel		Terminals: Brass
	Rear Housing: Nylon		Contacts: Silver "on-lay" Copper / Brass
	Terminal Screws: Steel & Yellow Passivated		Earth Strap: Mild Steel
Internal Busbars: Formed Pressed Brass		Frequency (Hz)	50
Rated Voltage (V~) (Ue)	250		
Resistive Load Rating (A)	13		
Termination Type	Screw		
Terminal Size (mm)	Ø5		
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4		
Double Pole Switch	Yes		
Supplied Back Box Depth (mm)	40		
Back Box Knockouts - Total (mm)	5 x Ø20		
Back Box Knockouts - Top (mm)	2 x Ø20		
Back Box Knockouts - Bottom (mm)	1 x Ø20		
Back Box Earth Terminal Supplied	Yes		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		
Terminal Torque Value (Nm)	2		
Back Box Knockouts - Sides (mm)	1 x Ø20		
Back Box Knockouts - Rear (mm)	None		
Standards	BS 1363-2		
Additional Information	For cleaning / polishing of products, use only a soft, dry, clean cloth.		
	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.		
	Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.		