essentials™

Product Code: CL050

Technical Specification

Description: 13A Fused Connection Unit With Optional Flex Outlet



General Information

80 (W) x 80 (H) x 42 (D) Dimensions (mm)

Plate Fixing Centres - Horizontal (mm) 60.3

> Style Metal Clad Finish Metal Clad Grey

Front Plate & Mounting Box: Materials

Electrophoretically Coated Steel

Terminals: Brass

Internal Busbars: Formed Pressed Brass

Rated Voltage (V~) (Ue)

Resistive Load Rating (A) 13

Fuse Fitted Rating & Type 13A (BS 1362)

> Termination Type Screw

Ø5 Terminal Size (mm)

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Switched No Yes

Twin Earth Terminals Flex Outlet Available Yes

Flex Outlet Location Front of Plate

Supplied Back Box Depth (mm)

Back Box Knockouts - Total (mm) 5 x Ø20

Back Box Knockouts - Top (mm) 2 x Ø20 Back Box Knockouts - Bottom (mm) 1 x Ø20

Back Box Earth Terminal Supplied Yes Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 1363-4

BS 1362

For cleaning / polishing of products, use only a soft, dry, clean cloth. **Additional Information**

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.





Insert, Fuse Drawer & Housing: Urea

Earth Strap: Mild Steel

Terminal Torque Value (Nm) 2

Flex Outlet Dimension (mm)

Back Box Knockouts - Sides (mm)

Back Box Knockouts - Rear (mm)

Frequency (Hz) 50

Terminal Screws: Steel & Yellow Passivated

