

Product Code: MD046PW

Description: 13A/10AX Double Pole Keyswitch Module



General Information

| | | |
|---------------------------------|---|---|
| Dimensions (mm) | 25 (W) x 52.5 (H) x 20 (D) | |
| Finish | Polar White | |
| Materials | Cover & Rocker Switch: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass | Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass |
| Anti Microbial Certified | Yes | |
| Rated Voltage (V~) (Ue) | 250 | Frequency (Hz) 50 |
| Inductive Load Rating (AX) | 10 | |
| Load Rating Comments | Suitable for Inductive Loads | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø3.5 | Terminal Torque Value (Nm) 0.5 |
| Terminal Capacity - Solid (mm²) | 4 x 1.5 or 2 x 2.5 | |
| Modular Rocker Switches | Yes | |
| Double Pole Switch | Yes | |
| Keyswitch | Yes | |
| Minimum Back Box Depth (mm) | 16 (25 Flat Plate) | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges