

Technical Specification



Product Code: MD075WH **Description:** 10A 3 Position Retractive Switch Module





Frequency (Hz) 50

General Information

25 (W) x 57 (H) x 27 (D) Dimensions (mm)

> Finish Click White

Materials Rocker Switch: Urea

Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Terminals: Brass

Internal Busbars: Formed Pressed Brass Contacts: Silver "on-lay" Copper / Brass

Anti Microbial Certified

Rated Voltage (V~) (Ue) 250

Resistive Load Rating (A) 10

> Termination Type Screw

Terminal Size (mm) Ø3.5 Terminal Torque Value (Nm) 0.5

Terminal Capacity - Solid (mm²) 4 x 1.5 or 2 x 2.5

> Modular Rocker Switches Yes 1 Pole 3 Position Switch Yes

Retractive Contact Options Press to Make Minimum Back Box Depth (mm) 25 (35 Flat Plate)

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS EN 60669-1

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches both the Deco white range and Metal Clad range.



E: sales@scolmore.com | W: scolmore.com