

Product Code: CL202

Description: 45A 2 Gang (Vertical) Double Pole Plate Switch



General Information

Dimensions (mm)	80 (W) x 140 (H) x 52 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Metal Clad	
Finish	Metal Clad Grey	
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel	Insert, Switch & Rear Housing: Urea Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	45	
Termination Type	Screw	
Terminal Size (mm)	Ø6	Terminal Torque Value (Nm) 2.5
Terminal Capacity - Solid (mm²)	1 x 16	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Product Marking	On & Off	
Supplied Back Box Depth (mm)	50	
Back Box Knockouts - Total (mm)	7 x Ø20	Back Box Knockouts - Sides (mm) 1 x Ø20
Back Box Knockouts - Top (mm)	3 x Ø20	Back Box Knockouts - Rear (mm) None
Back Box Knockouts - Bottom (mm)	2 x Ø20	
Back Box Earth Terminal Supplied	Yes	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS EN 60669-1

Additional Information	For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
-------------------------------	--