

Product Code: MD9125CH

Description: 10AX Intermediate Toggle Switch Module



General Information

Dimensions (mm)	25 (W) x 62 (H) x 22 (D)	
Finish	Polished Chrome	
Materials	Body: Nylon Terminal Screws: Brass	Terminals: Brass Switch Front & Nut: Cast Zinc
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable for Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	4.9 x 4.1	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
2 Way Switch	Yes	
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Suitable for Polished Chrome finish plates in Deco, Deco Plus, Define and Definity ranges.